

TECHNICAL REPORT



Maxwell Road, Stevenage
Hertfordshire
SG1 2EW, UK

T: +44(0) 1438 777 700
F: +44(0) 1438 777 800
E: info@fira.co.uk
W: www.fira.co.uk

SUSCOM INDUSTRIES LTD

Unit 8 Leopold Street
Lamberhead Industrial Estate
Pemberton
Wigan
WN5 8DH

Our Ref: **TSSEF62121**

Date: 28 October 2015

Delivery Date: 27 October 2015

Test Dates: 27 October 2015

For the attention of Tino Tartaglione

SAMPLE FOR TEST:

One, B-1- 640 X1 Base

TEST REQUIREMENT:

ANSI/BIFMA X5.1: 2011 – Clause 7: Base Test Static Load

RESULT :

PASS

This Report relates to the sample(s) submitted for test and no others. Additions, deletions or alterations are not permitted.

Test reports are given to the client in confidence, and may only be reproduced in whole or in part with written permission from FIRA International Limited. Note that the words "**tested by FIRA**" may be used in subsequent publicity for the product; "approved" must **not** be used.

Tests are carried out on the understanding that neither FIRA International Limited nor its officers can accept any legal responsibility for information or advice given or opinions expressed whether in response to specific enquiries or otherwise.

This Report is given subject to the Terms of Business of FIRA International Limited which are available at www.fira.co.uk/document/fira-testing-terms-and-conditionspdf.pdf.

TECHNICAL REPORT

DESCRIPTION

Item: B-1- 640 X1 Base
Supplied by: Suscom Industries Ltd
See Photos: One – Two

A 26" nylon 5 star base with an average thickness of 3.2mm.
The underside of the base was strengthened by ribbing

Sample Weight:

1.5 kg.

All dimensions are approximate.

TECHNICAL REPORT

ANSI/BIFMA X5.1: 2011

Section 7 – Base Test Static Load

The strength tests required were carried out in accordance with the standard. Where applicable details of the loads applied and their positions of application are retained at FIRA and are available on request.

Item: B-1- 640 X1 Base

Initial Inspection: No Apparent Faults

Result

B-1- 640 X1 Base	PASS
------------------	------

PRECONDITIONING AND MOISTURE CONTENT

FIRA cannot validate date of manufacture and therefore it is assumed that at least 4 weeks has elapsed between date of manufacture and delivery to FIRA. Unless otherwise stated on the first page of this report the sample was stored in indoor ambient conditions for at least the minimum duration as required by this standard prior to test. Wherever possible timber moisture content is verified prior to test. Where this is not possible the moisture content is assumed to be in the range 8 – 12 %.

TECHNICAL REPORT

CONCLUSION

The B-1- 640 X1 Base, as previously described, successfully satisfied the applicable test requirements of the Base Static Load Test: Clause 7 to ANSI/BIFMA X5.1: 2011.

Tested by: A Uddin

Reported By: S Hackett

Approved by: L Morey
Technical Specialist

TECHNICAL REPORT



Photo 1: B-1- 640 X1 Base



Photo 2: Underside of B-1- 640 X1 Base

****End of Report****